

Aquastream®

Thermostatic integral power shower system



- Suitable for exposed or concealed pipework
- Top, bottom or rear entry
- 2 speed, high performance flow rate
- Separate control of flow and temperature
- Quiet, low voltage operation
- 3 year comprehensive manufacturers guarantee

Fixing data:

Inlets	Gravity fed supplies only. 15mm "push fit" connections. Top entry centres 32mm. Bottom entry centres 50mm. Rear entry centres 65mm. Pipe projections for rear entry 50mm-60mm.
Max Inlet Pressure	1 bar - Must not be fitted to a mains supply.

Siting

"Easy fit" template supplied.
Operates in "negative head" situation.
However top of mixer unit must always be lower than base of cold storage cistern.

Transformer

Supplied with 2 metres mains cable and 4 metres of low voltage cable.

Pipework

Generally 15mm throughout.
"Full way" isolating valves MUST be fitted to inlet supplies.

Flow rate

Normal 10ltr min
Boost 18ltr min at 1 metre head.


Electrical info

Fuse size 3Amp in fuse spur

Pump rating

15 minutes in the hour

Dimensions (mm)



Installation Guide

Refer to installation guide.

Order codes

Thermostatic integral power shower system

Product no.	813.40.01 Satin chrome
Product no.	813.40.21 White/chrome
Product no.	813.40.20 White